

SCREENING BUCKET (BH-SCB)

BH-SCB

ALL RIGHTS RESERVED, SUBJECT TO REVISION



PRODUCT IMAGE

DESCRIPTION:

The screening bucket is an attachment for the excavators, loaders, skid steers and backhoe loaders that help the selection of natural material for different purposes at the jobsite.

Uses:

Screening Buckets are often used for Selection & Screening & Separation of natural materials, both before & after Crushing Phase. Screening buckets are used for ideal separation of Soil, Demolition, Construction, Waste, Turf, and Roofs & Compost

Technical Specification

	Unit	BH-SCB 10	BH-SCB 20	BH-SCB 30	BH-SCB 40
Recommended Carrier Weight	Ton	8-13	12-18	16-30	30-45
Mouth Width	mm	860	1100	1260	1340
Total Width	mm	1220	1485	1650	1835
Bucket Capacity	m ³	0.40	0.70	1.00	1.80
Screening Area	m ²	0.56	0.80	1.00	1.36
Shaft Travel	mm	40	40	40	40
No. of Screening Shafts	N ^o	2	2	2	3
Operating Weight	Kg	965	1400	1845	2725
Required Oil Flow	l/min.	90-125	100-150	165-220	180-280
Max. Required Oil Pressure	Bar	250	250	250	250

Advantages:

1. Quick adjustment of output size
2. Effective with wet material
3. High productivity
4. Simple operation
5. Easy loading
6. Easily replaceable screening tools